

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number  
**WO 2004/046550 A1**

(51) International Patent Classification<sup>7</sup>: **F04B 35/04**

(74) Agent: **DANNEMANN, SIEMSEN, BIGLER & IPANEMA MOREIRA**; Rua Marquês de Olinda, 70, 22251-040 Rio de Janeiro, RJ (BR).

(21) International Application Number:  
PCT/BR2002/000158

(22) International Filing Date:  
19 November 2002 (19.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **EMPRESA BRASILEIRA DE COMPRESSORES S.A.-EMBRACO** [BR/BR]; Rua Rui Barbosa, 1020, CEP-89219-901 Joinville, SC (BR).


(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:  
— with international search report

[Continued on next page]

(54) Title: A CONTROL SYSTEM FOR THE MOVEMENT OF A PISTON



(57) Abstract: A control system is provided for controlling the movement of the piston (10) of the fluid-pumping device (1), the piston (10) being displaceable in a block (5) of the fluid-pumping device (5) and being driven by a motor (2) fed by a voltage (V), comprising a semiconductor electronic system (T) cyclically applying the voltage (V) to the motor (2) to move the piston (10), a resistive element (Rb), a capacitive element (Cy), a piston-position sensor (S) to indicate the passage of the piston (10) by a point (R) at the block (5), the capacitive element (Cy) being charged by means of the resistive element (Rb), at each cycle of application of voltage (V) to the motor (2), the capacitive element (Cy) being discharged, at least partly, when the piston (10) passes by the point (R).

WO 2004/046550 A1